

years years year

DOME

CFDome 🕾

YOUR POOL WORK-SITES SHELTER

- + Protects from wind and rain.
- + Insulates against cold and protects from sun.
- + Easy to transport.
- + Installation in less than 5 minutes by 2 people.
- \cdot Dome in translucent grey 210 g/m² Oxford Cloth + PVC underskirt for the part in contact with the ground.
- 2 offset entrances separated by a transparent Velcro® closing door flap.
- PVC skirting for placing ballasts.
- Can be connected to a standard 220 V (15 A) outlet.
- · Easy handling thanks to its transport case.

Awning extension in option: attached to the dome with Velcro® and to be held to the ground by ballasts, it protects an outside stairway or a flap going beyond the dome.

BUY OR LEASE-TO-BUY*

* Financing available according to the country. Ask your distributor.



Transport case

L size CFDome - ref. CFDOME95	XL size CFDome - ref. CFDOME126	xxL size CFDome - ref. CFDOME156
 5 m (width) x 9 m (length) inside,	 6 m (width) x 12 m (length) inside,	 6 m (width) x 15 m (length) inside,
2 m (height) outside. Weight: 80 kg. Equipped with 6 x 200 W blower fans.	2 m (height) outside. Weight: 110 kg. Equipped with 8 x 200 W blower fans.	2 m (height) outside. Weight: 125 kg. Equipped with 10 x 200 W blower fans.
Awning extension/tarpaulin 8.80 x 3.90 m:	Awning extension/tarpaulin 9.60 x 4.00 m:	Awning extension/tarpaulin 9.60 x 4.00 m:
ref. EXTCFDOME3	ref. EXTCFDOME3XL	ref. EXTCFDOME3XL
To be contacted —		