

2023 WARRANTIES

BUBBLE COVERS / FOAM COVERS

ALVEOLAR BLACK, ALVEOLAR TRANSLUCENT BLUE, ENERGYGUARD 2, SOLGUARD, EXTRASUN, SUNDOWN, MIDNIGHT, ISODEL



550 micron bubble covers with "Alveolar" technology" are warrantied for 4 summer seasons with a degressive rate of 25%.

500 micron bubble covers with "Geobubble technology" are warrantied for 6 summer seasons with a degressive rate of 15%.

400 micron bubble Extrasun covers, Sundown cover and Midnight cover with "Geobubble technology" are warrantied for 3 summer seasons with a degressive rate of 30%.

Isodel covers are warrantied for 2 years in normal conditions of use (temperature < 30°).

The wearing of coping or the area around the pool is not covered by the warranty.

CRYSTAL BLUE, BLUE BLUE, SILVER BLUE, TRANSLUCENT GREY, OPAQUE GREY



500 micron summer covers are warrantied for 3 years with a degressive rate of 30%.

400 micron summer covers are warrantied for 2 years with a degressive rate of 50%.

ALVEOLAR BLACK, ALVEOLAR TRANSLUCENT BLUE, ENERGYGUARD 2, SOLGUARD, EXTRASUN, SUNDOWN, MIDNIGHT, BLUE CRYSTAL, BLUE BLUE, BLUE SILVER, TRANSLUCENT GREY, OPAQUE GREY, ISODEL



These covers must be protected with a protective tarpaulin when they are not on the pool. These covers must be placed away from frost in winter.

The wearing of coping or the area around the pool is not covered by the warranty. Dimensional stability: 1%.

Do not leave the bubble cover on during shock treatment (48 hours).

Rinse the cover using clean water 2 to 3 times per season. Before taking it in for winter, rinse thoroughly and leave to dry.

Summer cover water treatment: in compliance with applicable legislation (French decree n° 81324 of 7.4.81), swimming pool water treated with chlorine must comply with the following values: pH between 6.9 et 7.7 active free chlorine between 0.4 and 1.4 mg/l - combined chlorine max 0.6 mg/l - TH and TAC between 10 and 30°f.

Foam cover water treatment: in compliance with applicable legislation (French decree n° 81324 of 7.4.81), swimming pool water treated with chlorine must comply with the following values: pH between 6.9 et 7.7 active free chlorine between 0.4 and 1.4 mg/l - combined chlorine max 0.6 mg/l - TH and TAC between 10 and 30°f.

Never use the Isodel cover or summer covers for outdoor overflow pools because of the surface area exposed to the wind (unless previously agreed with our technical service).

Log on to <https://www.del-piscine.fr/en/> to view all our guarantees.