

EN

INSTALLATION GUIDELINES

INSTALLATION/SERVICING/MAINTENANCE/SAFETY ADVICE



DEL 

ABOVE-GROUND COVER

ROLLEASY 2

CONTENTS

PLEASE READ THESE INSTRUCTIONS CAREFULLY AND KEEP THEM FOR FUTURE REFERENCE

Please read this manual carefully to help you understand all of the information and to ensure safe installation, use and servicing. We cannot be held liable for any damage arising due to a failure to respect the instructions set out in this manual.

INFORMATION	p. 3
Electrical and solar-powered version	p. 3
Manual version.....	p. 3
DESCRIPTION	p. 4-6
Components provided	p. 4-5
Tools required for Mounting.....	p. 6
Packing list	p. 6
INSTALLATION	p. 7-14
Roller Mounting and fastening.....	p. 7-10
Control box.....	p. 11
Panneaux solaires	p. 12
Wiring for electrical version.....	p. 13
Wiring for solar-powered version	p. 14
Setting	p. 15
SERVICING/MAINTENANCE	p. 16-17
Pool water level.....	p. 16
Water filtration and treatment	p. 16
Servicing (customer's responsibility)	p. 16
Battery	p. 17
Wintering.....	p. 17
Maintenance	p. 17
Roller clutch.....	p. 18
SAFETY ADVICE AND STANDARDS	p. 19-20
RECYCLING	p. 21

INFORMATION


ELECTRICAL AND SOLAR-POWERED VERSION

The motor is located in the tube and can be accessed from inside the end-stand.. Power is supplied via an Control box located in the machine room or via 2 batteries placed in the terminal on the motor side for the solar-powered version. Programming the limit switches is carried out on the motor.

MANUAL VERSION

Unwinding and rewinding operations are carried out using the removeable wheel.




The slats is made of articulated waterproof slats that float on the surface of the water.



- On infinity pools, DEL covers cannot be compatible unless the pool is equipped with a Vitalia INFINITY kit to automatically lower the water level by at least 2cm when the pool cover is closed.
- Currently, DEL covers including a removable slats for step unit on the length to go over a ladder do not comply with standard NF P90-308
- Unless the alarm manufacturer indicates otherwise, immersion alarms are not compatible with DEL covers.


DESCRIPTION

COMPONENTS PROVIDED


	<ul style="list-style-type: none"> • The motor (which complies with electrical standards) is located in the tube and can be accessed from inside the end-stand.. • The “mechanical end switches” that allow the slats to be stopped when it has been fully unwound or wound onto the pole can be calibrated directly on the motor.
	<p>Control:</p> <ul style="list-style-type: none"> • Key switch
	<ul style="list-style-type: none"> • For the electrical version: The control box is installed in the technical room close to the pool.
	<ul style="list-style-type: none"> • For the solar powered version: The solar panels and the batteries are integrated into the terminal.
<p>Optional:</p>	
	<ul style="list-style-type: none"> • “Electrolyser coupling” (electrical version only): <p>“Stop salt” control box : connected to the control box of the cover and the electrolyser and is used to automatically reduce the production of chlorine when the pool is closed.(only applies to compatible electrolyzers).</p>

DESCRIPTION


COMPONENTS PROVIDED



MOUNTING PACKING FOR ELECTRICAL OR SOLAR-POWERED VERSION



MOUNTING PACKING MANUAL VERSION



DESCRIPTION

TOOLS REQUIRED FOR MOUNTING



PACKING LIST

Example for a 4x8m pool:
1 parcel - 0.80 x 0.60 x 0.55m 40kg
1 parcel - 4.30 x 0.20 x 0.20m 25kg
4 parcels - 4.10 x 0.25 x 0.20m 150kg
Total weight : 215kg

MOUNTING



2 people




3 hours

INSTALLATION

ROLLER MOUNTING AND FASTENING




MOUNTING OF TERMINAL

Remove the door of the terminals



INSTALLATION

MOUNTING AND POSITIONING OF THE ROLLER WITH REGARD TO THE POOL



INSTALLATION

▶ GROUND MOUNTINGS FOR ROLLER



Ø12 Rawlplug x3		M8x80 Step bolt x3		M8 Ø24x2 washer x3	
------------------------------	---	---------------------------------	---	---------------------------------	---



Ø12

Solar-powered and electrical version


adjusting
ring



x1

TF bolt
M3x16


x2



Free side


INSTALLATION

▶ INSTALLATION OF THE MOTOR (ELECTRICAL AND SOLAR-POWERED VERSION)



align the pin with the slot

Make gentle rotating movements with the motor to ensure it fits snugly into its housing.



INSTALLATION

CONTROL BOX

The electrical connection of the equipment must only be carried out by a qualified professional, and they must comply with the manufacturer's instructions in addition to the following applicable standards and regulations:

- NF C15-100: Low voltage electrical installations
- CEI 60364: Electrical installations for buildings

Please refer to the leaflet enclosed with the control box to ensure correct installation.



Incorrect installation may result in an electric shock, or it may even damage the equipment. We recommend that you disconnect the control box prior to any work being carried out on it.

Any specific electrical supply line must be protected by a 30mA circuit breaker along with a sufficient overcurrent protection kit.

We recommend use of shielded cable with a nominal cross-section that is not lower than the one indicated in the following table:

Current specified for the equipment A	Nominal cross-section mm ²
≤ 0.2	Flat twin tinsel cord a
> 0.2 and ≤ 3	0.5 a
> 3 and ≤ 6	0.75
> 6 and ≤ 10	1.0 (0.75) b
> 10 and ≤ 16	1.5 (1.0) b
> 16 and ≤ 25	2.5
> 25 and ≤ 32	4
> 32 and ≤ 40	6
> 40 and ≤ 63	10



NOTE: For power cables supplied with polyphase equipment, the nominal cross-section of the conductors is based on the maximum cross-section of the phase conductors at the end of the power cable that is intended to be connected to the terminals of the unit.

- a These cables can only be used if their length, as measured between the point where the cable or cable protector enters the equipment and the connection to the mains supply, does not exceed 2m.
- b Cables that have the cross-sections indicated in supports can be used for mobile equipment if their length does not exceed 2m.

INSTALLATION

SOLAR PANELS

To avoid potential breakage of the solar panel during transport, we have installed them on the inside of the door. They must therefore be mounted on the outside as shown below.




! Tighten by hand and stop on contact



INSTALLATION

WIRING FOR SOLAR-POWERED VERSION




INSTALLATION


- ❗ Any person carrying out work on the electrical parts must be qualified and wear PPE (personal protective equipment): gloves, goggles, mat, etc.
- ❗ Warning: use of the pool cover control buttons present in the housing (Wi-Key receiver) must only be carried out by a person who is absolutely certain that there is no risk and that no-one will enter the pool during the operation.

SETTINGS



CHECK



If the control logic is not respected, check the wiring of the installation.



PROGRAMMING THE LIMIT SWITCHES



By turning in the + direction, you will increase the range of movement of the cover.
By turning in the - direction, you will decrease the range of movement of the cover.

SERVICING/MAINTENANCE

POOL WATER LEVEL

- In order to ensure maximum safety and correct operation of the Roller, always check that the water level in the pool remains constant and complies with the manufacturer's requirements (for greater comfort, use an overflow and a water level regulator).
- A water level that is too high is due to the overflow being obstructed by leaves or other items.
- A water level that is too low means that there is a risk of blockage.
- In case of a recess or a handrail, the water level must be controlled by a level regulator.

WATER FILTRATION AND TREATMENT

- Programme filtration to take place at a time when the sun is shining on the pool and ensure that it is set to work continuously when the water reaches 28°C.
- In order to ensure that your installation will last, the water in the pool must be correctly treated in compliance with the applicable standards and recommendations (NF EN 16713-3).
- The pH, hardness and alkali levels of the water must be checked and adjusted as often as is necessary (although you will need to ensure that you don't correct these three parameters independently of each other but do so using the Taylor table and balance the water with regard to the three parameters analysed).

SERVICING (customer's responsibility)

- Carry out a deep clean of the slats twice per year (the first time in the year it is used and prior to wintering). This is even more important if the water in the pool is hard. To do so, use a pressure washer with hot water and a descaling cleaning product (Décalcit super).
- Also ensure that you regularly clean the fastening kits especially the anchor to avoid it getting stuck. We recommend annual greasing of the anchor to ensure that the system works as well as possible.
- It is best to inspect the entire system if the cover is forced to bear unexpected weight at any time (if anything falls on it).
- Carry out an annual check of the straps.
- For optimal solar sensor performance, clean it regularly using a window cleaning product.

SERVICING/MAINTENANCE

BATTERIES

At the first sign of the batteries losing power, recharge them.

NEVER LET THE BATTERIES LOSE COMPLETELY THEIR CHARGE.



Always disconnect the solar collectors beforehand then disconnect the batteries.

Connect the batteries to the charger (check the polarity). Plug the charger in. It will switch on automatically to the correct voltage and the charging process will begin. The red LED shows that charging is underway. When the charge is complete, the red LED will be switched off and the batteries are then powered by a maintenance charge (see charger instructions).

Precaution: Keep your charger in a dry place. Do not recharge the batteries close to the pool, but instead do so in a dry place.

Minimum recharging time: 48 hrs


MAINTENANCE

- All interventions must be carried out by a professional, who will contact the manufacturer if necessary.
- All spare parts must come from the manufacturer or comply with applicable standards.
- Inspect the cover thoroughly.
- It is necessary to check at the start of every season and if any accident has occurred (if anything has fallen onto the cover, if hail has struck the cover, if the cover has had to bear any abnormal weight etc...) check that none of the slats has sustained any visible damage that may affect the safety of the cover (cracked slats, holes, deformations, etc...). Make sure that you change the slats or the entire cover if required.
- In summer or in winter: do not place an opaque sheet over the cover: this may damage the slats due to high temperature.
- Check the state of the straps (seams) and in particular the wear on the anti-abrasion sleeve. If the latter is no longer fulfilling its role of protecting the strap against abrasions from the pool copings, then replace it

ROLLER CLUTCH

If the motor breaks down or if there is a power cut, you can remove the motor in order to close the pool manually.


1. Cut off electrical power
2. Disconnect the motor
3. Remove the mountings and pull out the motor
4. Unroll the slats manually
5. Attach the fastening kit



SERVICING/MAINTENANCE

WINTERING

- Position the cover in the closed position and keep the water level constant in accordance with the manufacturer's recommendations.



- During the winter season, in the event of snowfall, it is essential to remove snow from the roof using a brush with a telescopic handle.
- Snow should be removed from the cover using a blunt tool (such as a synthetic floor brush or broom).
- Winterise the pool according to its geographical location.
- Close the cover in the safety position.
- Leave the batteries connected to the reel and do not cover the solar panel.
- We recommend installing an Ivernéa winter cover or an Ivernéa Plus protective cover to protect the cover from UV rays and dirt.

SPARE PARTS

Online catalogue :



<https://www.my-cfgroup.fr/fr/pièces-detachees>

SAFETY ADVICE

Please read the recommendations set out below with care.

WARNING

Swimming pools can represent a serious danger for your children. Drowning can happen very quickly.

Children who are close to a swimming pool need to be watched constantly and actively, even if they know how to swim.

Learn lifesaving skills.

The physical presence of an adult is absolutely essential whenever the pool is open.



Memorise the telephone numbers for the emergency services and ensure that they are displayed close to the pool.

18 (in France) or **112**

FIRE SERVICE

15

**AMBULANCE
SERVICE**

(write the number that applies in your region)



POISON CONTROL

CENTRE

SAFETY ADVICE

- This cover is by no means a replacement for common sense or individual responsibility. Its aim is not to replace the vigilance of parents and/or responsible adults, who remain the essential factor in ensuring the protection of young children.
- **WARNING:** safety is only guaranteed when the cover is closed, locked and correctly installed in compliance with the manufacturer's instructions.
- The cover must systematically be closed if you are absent from home, even for a very short period.
- Check that no people and no foreign objects are in the pool before and during opening and closing operations.
- Make sure that you place all of the tools required for moving the pool cover out of the reach of children (e.g. the key).
- The operation of the mechanism must only be carried out by a responsible adult.
- Climbing, walking or jumping on a pool cover is strictly forbidden.
- In the following cases, take all necessary precautions to prevent young children from accessing the pool :
 - if you are waiting for repairs
 - if you notice any malfunction
 - if you cannot close or secure the pool
 - if the equipment is temporarily unavailable
- Respect the water levels indicated by the manufacturer.

A child can drown in less than 3 minutes, no type of protection can ever replace the watchful eye and vigilance of a responsible adult.

RECYCLING

PACKAGING



Dispose of the packaging in line with current rules and regulations.

END OF LIFECYCLE



- Do not put your scrapped equipment or used batteries in with unsorted household waste.
- You are responsible for disposing of all of your waste, in particular electrical and electronic equipment by taking it to a collection point where recycling and valorisation are carried out.
- Some products may contain substances that are dangerous for the environment. You need to ensure that these are eliminated or neutralised.
- Make sure that you are aware of all existing recovery and collection systems.



discard the manual in line with the current regulations.



Adresses sur quefairedemesdechets.fr

REGULATIONS

STANDARD

- This cover complies with standard NFP 90-308.

WARRANTY CONDITION

log on to www.del-piscine.fr to consult all our guarantees.



<https://www.del-piscine.fr/rechercher-une-garantie>

DEL SAS
ZA LA BASSE CROIX ROUGE
35530 BRÉCÉ - FRANCE

☎ +33 (0)9 70 72 5000 / INFO.FR@CF.GROUP

STAMP

A brand by CF group



ORIGINAL INSTRUCTIONS

A-DOTE03106.L1 / 12 2024