

A product by



CFTank | WATER RETENTION TANK

- + Prevents water wastage for total or partial emptying during renovations and maintenance work.
- + Quick installation and ultra simple to use.
- + Time saving (clamping can then be done immediately).

FEATURES

- 6 volumes: 1 m³, 2 m³, 5 m³, 10 m³, 20 m³, 30 m³.
- Weight: 900 g/m².
- Breaking strength: CH 400 / TR 308 daN 5 cm.
- Temperature resistance: from -30 °C à +70 °C.
- 100 % recyclable material: 905 F3 FERRARI brand.
- Fabric colour: RAL 6026 green.

★ STANDARD KIT COMPOSITION:

- A 160 mm diameter welded vent hatch with screw cap for easy access.
- A 1" threaded overflow on the top + threaded elbow fitting.
- A 1 1/2 tank outlet up to 5 m³ and 2" up to 30 m³.
- A PVC valve outlet on the side (to be mounted on the 1 1/2 or 2 "outlet): Ø 50 mm (up to 5 m³) or Ø 63 mm (from 10 m³).
- 4 tank reinforcement corners with stainless steel screws.
- A repair kit.

CF TANK references

- 1 m³: ref. CITERN1
- 2 m³: ref. CITERN2
- 5 m³: ref. CITERN5
- 10 m³: ref. CITERN10
- 20 m³: ref. CITERN20
- 30 m³: ref. CITERN30

★ OPTIONS:

Gravity-flow distribution kit
ref. KIT1CIT

Pump distribution kit
ref. KIT2CIT